



**GEARHEADS(ULTRA POWERFUL TYPE)** Frame size 90mm sq. (3.54 in. sq.)

BALL BEARING TYPE

▶ **RATED TORQUE OF GEARHEAD**

MODEL	Speed(rpm)	500	300	200	120	100	60	50	30	20	15	10	9	6	5	3	2	1
	Ratio	50Hz	3	5	7.5	12.5	15	25	30	50	75	100	150	166.7	250	300	500	750
60Hz		3.6	6	9	15	18	30	36	60	90	120	180	200	300	360	600	900	1800
<b>L9UK□B</b> <b>L9V10D(DECIMAL)</b>	kg-cm	22.8	38.1	57.1	85.8	102.9	155.1	186.1	300	300	300	300	300	300	300	300	300	300
	N-m	2.24	3.73	5.60	8.41	10.09	15.20	18.24	29.40	29.40	29.40	29.40	29.40	29.40	29.40	29.40	29.40	29.40
	oz-in	317	529	793	1191	1429	2154	2585	4166	4166	4166	4166	4166	4166	4166	4166	4166	4166

With Decimal Gearhead

- \* The normal torque is that the motor and gearhead are directly coupled.
- \* Insert the denominator of reduction ratio in □ of gearhead model name.
- \* Actual rotation speed is 2~15% less than synchronous speed.
- \*   Color indicates that the rotation of gearhead shaft is in opposite direction as output shaft of motor.


INDUCTION MOTORS

**DIMENSIONS**

Unit : mm(inch)

**DECIMAL GEARHEAD**

**L9V10D**




WEIGHT 0.6kg (1.3 lb)




**GEARHEAD**

**L9UK□B**



MODEL	GEAR RATIO	WEIGHT		BOLT
		kg	lb	
L9UK□B	1/3~1/200	1.95	4.3	M6xL20



KEY SIZE



**L9UK□B + L9I120P□H**

